

**This Page Is Inserted by IFW Operations
and is not a part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

12

EUROPEAN PATENT APPLICATION

21 Application number: 87305776.4

51 Int. Cl.⁴: B41J 27/18 , G01D 15/18

12 Date of filing: 30.06.87

The title of the invention has been amended
(Guidelines for Examination in the EPO, A-III,
7.3).

71 Applicant: Hewlett-Packard Company
Mail Stop 20 B-O 3000 Hanover Street
Palo Alto California 94304(US)

30 Priority: 01.07.86 US 880774

72 Inventor: Baker, Jeffrey P.
11469 Duenda Road
San Diego California 92127(US)
Inventor: Coverstone, Randy A.
6228 Escallonia Drive
Newark California 94560(US)
Inventor: Ton La, Duong
11292 Turtleback Court
San Diego California 92127(US)

43 Date of publication of application:
30.03.88 Bulletin 88/13

64 Designated Contracting States:
DE FR GB IT

74 Representative: Colgan, Stephen James et al
CARPMAELS & RANSFORD 43 Bloomsbury
Square
London WC1A 2RA.(GB)

54 Ink reservoir containing an absorbent foam for an ink jet printing device.

57 The novel pen body construction described herein includes multiple ink storage compartments (12, 14, 16) communicating with a multi-orifice printhead (20), and these compartments are adapted to receive sections of ink-storage foam (42, 44, 46). Preferably, this foam is a reticulated polyurethane foam of controlled porosity and capilarity and is especially well suited for storing different ink colors, such as cyan, magenta and yellow. However, single compartment black ink storage is also within the scope of this invention.




Fig 1

Thermal Ink Jet Pen Body Construction Having Improved Ink Storage and Feed Capability and Multicolor Ink Dispensing Capability and Low Cost Construction

Technical Field

This invention relates generally to thermal ink jet pen construction and more particularly to a single or multi-compartment pen body having improved ink storage and distribution capabilities.

Background Art

In the art of thermal ink jet printing, it is known to provide a bladder type of ink reservoir for supplying ink to a thermal ink jet printhead. The printhead will typically include a thin film resistor (TFR) substrate having a plurality of heater resistors therein, and a barrier layer and orifice plate member is usually mounted on top of the thin film resistor substrate. This member will typically include the ink reservoirs which are disposed above the heater resistors and further defines the corresponding drop generator nozzles for ejecting ink onto a print medium.

The bladder reservoir for supplying ink to the entire printhead may, for example, take the form of a rubber thimble which is located within the housing to which the thermal ink jet printhead is affixed. This type of reservoir and printhead construction is disclosed, for example, in the Hewlett Packard Journal, Volume 36, Number 5, May 1985, incorporated herein by reference.

Whereas these bladder type reservoirs have proven generally satisfactory for certain types of thermal ink jet (TIJ) printers, they nevertheless take up too much space and are unable to hold a sufficiently large volume of ink for other types of printer applications.

Disclosure of Invention

Accordingly, the general purpose of this invention is to provide new and improved pen body construction adapted for use in thermal ink jet printers. This new pen body construction represents a significant departure from the bladder-type ink storage approach and includes a novel printhead and ink storage structural arrangement. In this arrangement, the above problems associated with the ink storage and ink delivery mechanisms of the prior art have been either eliminated or substantially minimized.

To accomplish this purpose, we have discovered and developed a novel pen body construction which includes a certain ink storage foam which is preferably a controlled porosity polyurethane foam. This foam has been reticulated to break the walls of small membranes within the foam material and thereby increase the mobility of ink flow therein. The foam is also compressed to reduce the pore size therein to in turn reduce the foam thickness while increasing its density. In this manner, the desired capillarity of the foam can be controlled. By this process, the capillary force of the foam is increased and thereby renders this ink storage medium especially well suited for feeding ink to a thin film resistor type of thermal ink jet printhead. Furthermore, this ink feed apparatus is provided using a minimum of space (volume) to house the foam, and it features a corresponding maximum of ink storage capability in the foam. In addition, this polyurethane foam is economical to provide and is particularly adaptable for insertion into separate adjacent compartments of a pen body housing. This housing may then be used to store ink in various colors, such as cyan, magenta, and yellow, in a disposable pen body according to one embodiment of the invention.

The various advantages and novel features of this pen body construction will become more readily apparent in the following description of the accompanying drawing.

Brief Description of the Drawings

Figure 1 is an exploded view of the pen body construction according to one embodiment of the invention; and

Figure 2 is a cross section view taken along lines 2-2 of Figure 1.

Best Mode for Carrying Out the Invention

Referring now to Figure 1, there is shown a three compartment pen body designated generally as 10 and having three (3) ink storage compartments 12, 14 and 16 therein as indicated by the dashed line divider partitions within the interior of the body 10. The pen body 10 further includes an output printhead support surface 18 which is joined to upstanding side walls 20 in a rectangular recep-

tacle configuration. This structure further includes three (3) ink output ports 22, 24 and 26 respectively communicating with the three ink storage compartments 12, 14 and 16.

The rectangular support receptacle 18 is configured to receive a thin film resistor type printhead 28 having a plurality of ink ejection orifice groups 30, 32 and 34 respectively which are circular in geometry and which communicate with the ink flow passages 22, 24 and 26 extending to the surface 18 of the rectangular support receptacle.

In the assembly of Figure 1, three ink filters 36, 38 and 40 are mounted within the compartments 12, 14 and 16, respectively. These filters are typically constructed from stainless wire mesh of a desired porosity to provide good filtration of air bubbles and solid particles when passing ink from the three sections 42, 44 and 46 of polyurethane foam located in the three compartments 12, 14 and 16 of the pen body 10.

The back surface 48 of the foam body sections 42, 44 and 46 is fitted with a plug generally designated as 50, and this plug including its end cover 51 prevents back-pressure build up and facilitates the removal of ink from the foam and through the filters 36, 38 and 40 to the printhead 28. Air vents 52 are covered with porous plastic membranes 54 which prevent ink from leaking out through the air vents 52. The remaining structural detail of these three vents 52 and their intermediate wall partitions 66 and 68 is shown in a larger cross-section view in Figure 2 below. As previously indicated, the foam material of sections 42, 44 and 46 is a controlled porosity ether-type polyurethane foam which has been reticulated to break the membrane walls therein. This increases the capillary force of the foam and thereby renders it especially well suited for feeding ink along the ink feed paths to a thin film resistor thermal ink jet printhead. The plug 50 further includes foam compression tabs 56 which extend into the foam sections 42, 44 and 46 as shown and provide a desired amount of compressive forces to the foam for further increasing capillary forces in the foam and optimizing ink dispensation to the printhead.

The particular foam which has been used in actual practice is an ether-type foam material obtained from the Scott Paper Company of Philadelphia, Pennsylvania and had a porosity of between 60 and 75 pores per inch.

Referring now to Figure 2, the cross section view in this figure is taken along lines 2-2 of Figure 1 wherein like reference numerals have been used in both figures to identify the same components therein. The pen body 10 includes interior walls 82 and 64 which serve to partially define the three compartments for receiving the rectangular sections 42, 44 and 46 of foam as shown in Figure 1.

These interior walls 62 and 64 receive the corresponding T-shaped interior extensions 66 and 68 of the cover or end member 51 of the previously described end plug 50. This plug 50 further includes air vents 70, 72 and 74 which communicate with the cavities or recessed portions 76, 78 and 80 as shown. These recessed portions or cavities 76, 78 and 80 in the cover member 51 of the plug 50 receive a plurality of porous membranes 82, 84 and 54 which are fabricated from polytetrafluoroethylene (PTFE) and which provide adequate ventilation within the three compartments of foam. At the same time, these membranes 82, 82 and 54 are of sufficient mesh density to prevent ink back-flow through the three air vents 70, 72 and 74.

A plurality of ink chambers 88, 90 and 92 are provided as shown in the three ink pipes 94, 96 and 98, respectively, in the lower regions of the pen body 10. Each of these ink pipes 94, 96 and 98 are provided, respectively, with the three previously identified wire mesh filters 40, 38 and 36. These latter filters provide filtering of air bubbles and solid particles from the ink which ultimately passes through the ink pipes 88, 90 and 92 and to the TFR printhead 28. This ink flow path also includes the lateral ink passage located between the lower surface 100 of the pen body 10 and the facing surface of the semiconductor substrate member 102 of the TFR printhead substrate 28.

The geometrical configuration of the ink pipes 94, 96 and 98 in combination with the walls 62, 64 and 66 and the spacing therebetween beneath the foam increases the compression of the foam in the areas above the three filters. This fact in turn increases the capillarity of the foam in the region thereof above these three filters and thus reduces the possibility of air bubbles interrupting the ink path vertically down through the foam and into the three ink pipes 94, 96 and 98.

The substrate member 102 is bonded to a nozzle plate 104 by means of an adhesive barrier 106. This barrier 106 may advantageously be a selected polymer material such as the RISTON or VACREL trade name polymer materials made available by the E. I. DuPont Company of Wilmington, Delaware. The ink will flow vertically down through the ink pipes 88, 90 and 92 and then into the three vertical passages 108, 110 and 112 in the substrate member 102. These vertical passageways 108, 110 and 112 will then feed ink to the plurality of groups of orifices 30, 32 and 34 in the nozzle plate 104 and located in a circular pattern as shown.

The nozzle plate 104 may advantageously be electroformed of nickel and plated with gold and then affixed to the polymer barrier material 106 using, for example, the heat staking process disclosed and claimed in copending application serial number 861,192 of Stephen J. Nigro et al. This

application is entitled "Process For Manufacturing Thermal Ink Jet Printheads and Structures Produced Thereby", and is assigned to the present assignee and incorporated herein by reference. The nozzle plate 104 may be fabricated in the manner described in the above identified Hewlett Packard Journal, Vol. 38, No. 5 May 1985.

Finally, the thin film resistor structure 28 is secured to the bottom facing surface 100 of the pen body 10 by means of a suitable adhesive 114 which is disposed as shown at the outer periphery of the substrate 102, as well as at interior recessed wall surfaces 116 and 118 thereof.

The present invention is not limited to thermal ink jet applications and may instead be used in other types of ink jet applications in which the above foam storage-of-ink capability is desirable and compatible.

Industrial Applicability

The pen body according to this invention is useful in the manufacture of black and white and color printers and plotters operative in a variety of raster and vector modes.

Claims

1. An ink jet pen including, in combination:
 - a. a housing and support member having a support surface at one end thereof with openings for passing ink therethrough,
 - b. an ink jet printhead mounted on said support surface and having a plurality of ink ejection orifices communicating said opening in said support surface and,
 - c. a preselected absorbent foam material mounted within said housing and support member and operative to receive and retain a supply of ink for feeding said ink through openings in said support surface and to said thermal ink jet printhead.
2. The pen defined in claim 1 wherein said foam is a reticulated polyurethane foam.
3. The pen defined in claim 1 wherein said housing has three separate compartments therein for receiving three bodies of foam which function respectively to store three colors of ink such as cyan, magenta and yellow in a three color pen.
4. The pen defined in claim 3 wherein each compartment includes an ink pipe for feeding ink from said foam to said printhead, said ink pipe being located between vertical walls defining each compartment and spaced therefrom so as to increase the compressive forces on said foam in the region of said foam above each said ink pipe, whereby capillarity in said foam region is increased

and thereby reduces the possibility of air interrupting the ink path vertically down through said foam and into said ink pipe.

5. A process for feeding ink to an ink jet printhead which comprises the steps of:

- a. storing ink in a reticulated polyurethane foam of controlled capillary force, and

- b. bringing said foam into ink flow communication with said printhead, whereby ink is communicated from said foam to said printhead with a controlled capillary force.

6. The process defined in claim 5 which includes:

- a. providing said foam in three separate sections, and

- b. providing these sections with the ink colors of cyan, magenta and yellow, respectively, whereby a relatively low cost 3-color pen is provided with a high volume and high density ink storage capability.

7. The process defined in claim 5 wherein said foam is inserted into a single compartment pen body and filled with black ink.




Fig 1




Fig 2



European Patent
Office

EUROPEAN SEARCH REPORT

Application number

DOCUMENTS CONSIDERED TO BE RELEVANT			EP 87305776.4
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)
X	<u>US - A - 3 967 286 (ANDERSON)</u>	1,2,5,7	B 41 J 27/18
Y		3,6	G 01 D 15/18
A	* Column 1, line 48 - column 2, line 17; fig. 1 *	4	
	--		
Y	<u>EP - A1 - O 021 389 (SIEMENS)</u>	3,6	
	* Fig. 1; abstract *		

			TECHNICAL FIELDS SEARCHED (Int. Cl.4)
			B 41 J
			G 01 D
The present search report has been drawn up for all claims			
Place of search VIENNA		Date of completion of the search 06-10-1987	Examiner MEISTERLE
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone		T : theory or principle underlying the invention	
Y : particularly relevant if combined with another document of the same category		E : earlier patent document, but published on, or after the filing date	
A : technological background		D : document cited in the application	
O : non-written disclosure		L : document cited for other reasons	
P : intermediate document		A : member of the same patent family, corresponding document	